



GLUING SOLUTIONS



meler 



S-BEAM NOZZLES

- The S-BEAM Nozzle series for beads (dots and lines) guarantees application repeatability.
- A wide range of nozzle diameters and projection lengths facilitate the right nozzle selection for each application.
- The manufacturing process, subject to the highest quality standards, assures maximum dosage precision in each application.
- Nozzles can be exchanged easily maintaining the same level of performance at all times.
- A laser classification and marking system allows perfect identification of the selected nozzle type.

				
STF (STRAIGHT FIXED)	RA (RIGHT ANGLE STANDARD)	RAR (RIGHT ANGLE ROUND)	RAL (RIGHT ANGLE LONG)	STR (STRAIGHT ROTATABLE)
Number of outputs: 1	Number of outputs: 1 / 2	Number of outputs: 1 / ... / 8	Number of outputs: 1	Number of outputs: 1 / ... / 8
Length (projection): 1.3				Length (projection): 1.5
Diameter: 0.20 / 0.25 / 0.30 / 0.35 / 0.40 / 0.45 / 0.50				Diameter: 0.20 / 0.25 / 0.30 / 0.35 / 0.40 / 0.45 / 0.50 / 0.55 / 0.60 / 0.70 / 0.80 / 0.90 / 1.00
Length (projection): 1.9 / 4.0				—
Diameter: 0.20 / 0.25 / 0.30 / 0.35 / 0.40 / 0.45 / 0.50 / 0.55 / 0.60 / 0.70 / 0.80 / 0.90 / 1.00				—
—	—	—	Nozzle length: 15 / 20 / 25 / 30	—
—	Angle: 15 / 30 (two outputs)	Angle: 0 / ... / 180	—	Angle: 15 / 30 / 45 / 60 / 90 (L: line / C: circle)

For more information, contact your nearest Meler distributor:

meler 

Meler Gluing Solutions
Pol. Los Agustinos, c/G, nave D-43
E-31160 Orcoyen - Navarra - Spain
Phone: +34 948 351 110
Fax: +34 948 351 130
info@meler.eu

www.meler.eu

CE

